

Spesifikatsioon Halo 20

Supply Voltage: 10.5 - 31.2 VDC (12/24V systems)

Max Wind Speed: 100 knots (51 m/s)

Power Consumption typical: 18W

Operating Temperature Range: -25° to + 55°C

Power Consumption max: 20W

Max Range, scale: 24 NM

Beam width: 4.9° H x 25° V

Weight: 5.9 kg (13 lbs) without cable

Min Range, scale: 50 m / 200 ft / 50 yd

Dimensions Diameter: 510mm (20")

Dimensions W x H x D: 510mm dia x 223 mm H. (20" dia x 8.8" H)

Recommended Fuse Rating: 5A

Humidity: 95% RH at 35°C (95°F)

Approvals Compliance: FCC, Part 47 CFR 80 and 90: RED, Article 3 of Directive 99/5/EC:  
CE: EN, EN302-248 V2.1.1: Industry Canada, RSS238: RCM (C-Tick): IEC60945 Sec  
9.2,9.3, 10.3-10.9, 11.2: IEC60950 Electrical Safety

Radar Modes: Harbour, Offshore, Weather, North Up, Course Up, Relative motion, True Motion

Waterproofing: IPX6

Radar Technology: Pulse Compression

Interface: Simrad MFD

Rotation speed: 24 RPM